APPLICATION FOR
UNITED STATES PATENT
IN THE NAME OF

ARVIND B. IYER AND ASHUTOSH SINGLA

FOR

VLAN TO MPLS MAPPING: METHOD TO ESTABLISH END-TO-END TRAFFIC PATH SPANNING ENTERPRISE LOCAL AREA NETWORKS AND A GLOBAL NETWORK

Prepared By:

TITLE OF THE INVENTION

VLAN TO MPLS MAPPING: METHOD TO ESTABLISH END-TO-END TRAFFIC PATH

SPANNING ENTERPRISE LOCAL AREA NETWORKS AND A GLOBAL NETWORK

BACKGROUND OF THE INVENTION

1.   Field of the Invention

The present invention generally relates to communication in enterprise local area

networks (LAN) and a global network. More particularly, the present invention relates to

establishing an end-to-end virtual circuit that is secure and fast between a source enterprise local

area network, a global network, such as the Internet, and a destination enterprise LAN.

2.   Discussion of the Related Art

Data communication networks rely heavily on shared, packet-based technologies for both

access and backbone connections. Global networks, e.g., the Internet, comprised of routers,

hubs, and switches allow the connection of multiple LANs in a global environment. The Internet

routers or other similar devices are capable of processing packets having different protocols.

As the Internet has grown in popularity, many bandwidth intensive applications are

utilizing the Internet as a communication medium. Applications like videoconferencing and

Internet Protocol (IP) telephony require large amounts of bandwidth in order to perform at the

level required by their customers. The performance aspect of both videoconferencing and IP

telephony require not only large amounts of bandwidth but also guaranteed bandwidth. In

addition, these applications require security because users do not desire to have unwanted parties

eavesdropping on conversations or conferences. The data utilized by videoconferencing and IP

telephony applications needs to be available only to the users participating in the service and

must be passed from the source to the destination as quickly as possible to enable users to be

satisfied with the service.

The need for speed and security must be addressed in both the global network and the

local area networks where the source and destination endsystems are located. When the data

packets are travelling in the enterprise networks containing the source and destination

endsystems, virtual local area networks (VLANs) have provided both speed and security for the

data packets.

VLANs are the grouping of devices and endsystems on different physical LAN segments

that can communicate with each other as if they were all on the same physical LAN segment.

Fig. 1 illustrates a VLAN established in an enterprise local area network according to the prior

art. End systems 02, 04, 10, 16 are all part of VLAN 20 even though they reside on different

physical LAN segments.

VLANs are implemented through switches on the enterprise network. The creation of

VLANs allows the endsystems and devices on the VLAN to be grouped into a broadcast domain,

and the performance in the network is increased because broadcast traffic is limited to users

performing similar functions or within similar workgroups.

IP telephony and videoconferencing have driven the demand for increased and

guaranteed bandwidth in the backbone of the network. The popularity of the Internet has

required the Layer 3 (Network Layer) switching devices to handle Layer 3 routing in high-speed

switching hardware in order to keep pace with speed demands. Currently, the routing of packets

on the Internet is based on routing protocols utilizing algorithms to obtain the shortest path in the

Internet, and not taking into account such factors as delay or congestion.

Multiprotocol label switching (MPLS) is designed to be a versatile solution and to assist in the speed and security problems the Internet is facing. In MPLS, the transmission of data packets occurs over label-switched paths (LSPs). A sequence of labels is established from the source of the transmission to the destination at each and every node, e.g., router, along the path. The labels may be established based upon detection of a certain flow of data and may be distributed using a label distribution protocol (LDP) or piggybacking on existing routing protocols. Each data packet encapsulates and carries the labels from the ingress router to the egress router.

Multiprotocol label switching (MPLS) provides a virtual path capability between between routers to efficiently carry differentiated services across the Internet. High-speed switching is possible over the Internet if the routers are MPLS-enabled because the fixed-length labels are inserted at the very beginning of the packet or cell and are used by the routing hardware to switch the packet quickly between links. A transmission on a LSP is secure because only devices on the LSP interact and transfer the data.

Currently, however, the advantages of secure and fast connections are housed separately in the Internet and within the enterprise LANs. There is no feasible way to allow transmission from a source endsystem to a destination endsystem spanning a global network and multiple enterprise LANs. Accordingly, a need exists for a method and system to allow fast and secure communications for newly developed applications, such as IP telephony and videoconferencing.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 illustrates a virtual local area network established in an enterprise local area network according to the prior art;

Fig. 2(a) illustrates an end-to-end virtual circuit spanning enterprise local area networks and a global network according to an embodiment of the present invention;

Fig. 2(b) illustrates a virtual local area network in an end-to-end virtual circuit spanning enterprise local area networks and a global network according to an embodiment of the present invention;

Fig. 3 illustrates a local area network switch and associated ports according to an embodiment of the present invention;

Fig. 4 illustrates a network of multiprotocol label switched (MPLS)-enabled routers in a global network according to an embodiment of the present invention;

Fig. 5 illustrates a label-switched path on a global network according to an embodiment of the present invention;

Fig. 6 illustrates a plurality of routers including a label-switched path and the corresponding label information base tables for the label-switched path according to an embodiment of the present invention;

Fig. 7 illustrates transmission of a packet through an enterprise local area network including a plurality of switches by utilizing one virtual local area network (VLAN) and also by utilizing two VLANs according to an embodiment of the present invention;

Fig. 8 illustrates a virtual circuit with multiple enterprise local area networks connected by multiple routing segments according to an embodiment of the present invention; and

Fig. 9 illustrates an intermediate enterprise local area network's transmission of data packets from a preceding routing segment to a succeeding routing segment according to an embodiment of the invention.

DETAILED DESCRIPTION OF THE INVENTION

Fig. 2(a) illustrates an end-to-end virtual circuit spanning at least two enterprise local area networks (LANs) and a global network according to an embodiment of the present invention. The present invention establishes a fast and secure end-to-end virtual circuit from a source enterprise LAN to a destination enterprise LAN via a global network by mapping a multiprotocol labeling system (MPLS) tag to a virtual local area network identifier (VLAN-ID) and vice-versa. In other words, the MPLS-enabled routers and the corresponding label-switched path (LSP) are connected to the VLANs in each enterprise network to form the end-to-end virtual circuit (EEVC). The EEVC is established in one direction from source to destination. The same principles apply when a transmission is made in the opposite direction, e.g., original destination to original source, rather than source to destination, as is necessary in two-way communication applications like videoconferencing and IP telephony.

Fig. 2(a) illustrates a representative end-to-end virtual circuit (in bold arrows) that spans a source enterprise LAN, a global network, and a destination enterprise LAN according to an embodiment of the present invention. The source enterprise LAN includes a plurality of endsystems **30, 32, 36,** and **38** including a source endsystem **34** and a LAN switch S1 **40.** The global network includes a plurality of MPLS-enabled routers R1 **42,** R2 **44,** R3 **46,** and R4 **48.** The destination enterprise LAN includes a LAN switch S2 **50,** a LAN switch S3 **52,** a plurality of destination endsystems **54 58** including a destination endsystem **56** connected to the LAN switch S2 **50,** and a plurality of destination endsystems **60 62** connected to the LAN switch S3 **52.** The end-to-end virtual circuit (EEVC) includes only devices that are running the application for which the virtual circuit has been established. For example, if the application of the virtual circuit is a videoconference among endsystems **34, 38, 56** and **62,** then endsystems **34** and **38,**

5

LAN switch S1 **40**, routers R1 to R4 **42 44 46 48**, LAN switch S2 **50**, endsystem **56**, LAN switch

S3 **52**, and endsystem **62** form the EEVC for this particular application.

The first/source enterprise LAN includes the source endsystem **34**, the plurality of

additional endsystems **30 32 36 38**, and the LAN switch S1 **40**. A network administrator

establishes a VLAN on the source enterprise LAN by inputting information into a LAN switch's

VLAN-ID table. The protocol for establishing the VLAN-ID may be a general attributes

registration protocol (GARP) VLAN registration protocol, otherwise known as GVRP.

Alternatively, a software program may establish the VLAN-ID by inputting the information

automatically. The information includes what endsystems are included in each specific VLAN

(endsystem information), and also includes the port designation used to communicate with each

endsystem, switch, or device that is part of the VLAN (port designation information). In

another embodiment of the invention, the endsystem information and port designation

information each are contained in separate VLAN tables.

According to an embodiment of the present invention, a first leg of the virtual circuit is

completed by including a local edge router (LER) on the VLAN in the source enterprise LAN.

Alternatively, the LER may also be referred to as an ingress router. The local edge router is a

router that is located at the edge of the global network and directly communicates with a switch

on an enterprise LAN. In other words, the network administrator or software program maps the

VLAN-ID to the LER and includes the port that connects the switch to the LER in its VLAN port

designation information. Because the LER is included in the VLAN, the LER may receive

packets from the LAN switch because the LAN switch automatically transfers packets from any

device on the VLAN to all of the other devices on the VLAN.

For example, as illustrated in Fig. 2(b), the network administrator or software program

may construct a VLAN-ID table in LAN Switch S1 **40** for VLAN 15. VLAN 15 includes

endsystem **34**, endsystem **38**, LAN switch S1 **40,** and router R1 **42** (the LER or ingress router).

Fig. 3 illustrates a LAN switch and associated ports according to an embodiment of the present

invention. Endsystem **34** is connected to port 1 on LAN switch S1 **40**; endsystem **38** is

connected to port 3 on LAN switch S1 **40**; and router R1 **42** is connected to port 4 on LAN

switch S1 **40**. The VLAN table may include two sections of information: first, a mapping of

VLAN-IDs to endsystems; and second, a mapping of the ports designated for each VLAN-ID.

Illustrative tables for the embodiment discussed above are set forth below.

VLAN Endsystem Table for LAN Switch S1 40

Access Port	Devices Heard	VLAN-ID
1	34	15
3	38	15
4	42	15

VLAN – Port Designation Table for LAN Switch S1 40

VLAN-ID	ACCESS PORT
VLAN 15	1
VLAN 15	3
VLAN 15	4

When the LAN switch S1 **40** receives a packet from endsystem **34** (the source

endsystem), it retrieves from the endsystem table that VLAN-ID 15 is associated with endsystem

34. S1 **40** encapsulates the original packet with a VLAN header that contains a list of the VLAN-IDs with which the source endsystem **34** is associated with. In this example, the packet has a VLAN header indicating that it is to be transmitted to other devices on VLAN 15. LAN Switch S1 **40** also determines which ports are associated with VLAN 15 by accessing the VLAN-port designation table. After determining which ports are associated with VLAN 15, LAN Switch S1 **40** transmits the packet out of all the associated access ports except for the source port (in this case, port 1). Illustratively, the packet is sent out of access port 3 to endsystem **38** and out of access port 4 to router R1 **42.**

The packet is being transmitted to the edge of the global network quickly because the LAN switch S1 **40** needs only to access the VLAN tables before transferring the packet. In addition, the packet is transmitted securely because only the members of the VLAN (for example, teleconference members) receive the packet. In other words, the VLAN of the source enterprise LAN is now extended (or mapped) to the Local Edge Router R1 **42.** Each successive packet follows the path of the first packet.

The next leg on the end-to-end virtual circuit (EEVC) is through the global network, such as the Internet. Fig. 4 illustrates a group of MPLS-enabled routers in a global network according to an embodiment of the present invention. A network that is MPLS-enabled is referred to as an MPLS domain. Illustratively, the global network includes routers R1 **42,** R2 **44,** R3 **46,** R4 **48,** R5 **64,** R6 **66,** R7 **68,** R8 **70,** R9 **71,** R10 **72,** and R11 **73.** Using MPLS, the packets enter the global network at Router R1 **42** and exit the global network at Router R4 **48.** R1 **42** may be referred to as an ingress router; R4 **48** may be referred to as an egress router. Also, both R1 **42** and R4 **48** may be referred to as Local Edge Routers (LER) because the two routers are on the edges of the global network. On the global network, a packet may travel on many different paths

from R1 to R4. For example in Fig. 4, the packet(s) may travel from R1 **42** to R5 **64** to R6 **66** to R7 **68** to R4 **48,** or via any of a number of alternative routes.

When utilizing MPLS, the routing of the first packet determines the routing of successive packets and establishes the MPLS leg of the end-to-end virtual circuit or the virtual circuit in the global network. All packets with the same characteristics as the first packet travel through the global network utilizing the same MPLS virtual circuit established by the first packet.

When the packet first enters the global network at R1 **42**, the packet may be provided with an equivalence class. The assigning of an equivalence class allows each packet in a group to share the same transport requirements. In an embodiment of the invention, all packets transferred to the router R1 **42** via a specific port indicate the packets are being transferred on a VLAN and belong to one equivalence class.

In a MPLS domain, a path, commonly referred to as a label-switched path (LSP), is established for given packets to travel based on the equivalence class. The path of the first packet may establish the path for all of the packets with the same characteristics. The LSP may be established by "hop-by-hop" routing, where each router successively selects the next hop for the packets based upon a variety of factors. The routers may use any available routing protocols such as open shortest path first (OSPF), border gateway protocol (BGP), or asynchronous transfer mode (ATM) private network to network interface (PNNI) to establish the LSP. Alternatively, the LSP may be established by explicit routing where the ingress router, e.g., R1 **42,** specifies the list of nodes / routers through which the packet are to travel.

Fig. 5 illustrates the creation of a label-switched path (LSP) on the global network according to an embodiment of the present invention. If "hop-by-hop" routing is used and R2 **44** is chosen as the next router, then R1 **42** initiates a label request through R2 **44**. The request

continues through the network to the egress router, e.g., from R2 **44** to R3 **46** to R4 **48**. Each

intermediary router may receive a MPLS label from its downstream router: R3 **46** receives a

MPLS label from R4 **48** and R1 **42** receives a MPLS label from R2 **44**. The LSP is established

by the distribution of the MPLS labels. A label distribution protocol (LDP) or any other

signaling protocol may be used in establishing the LSP.

When a router receives a label from the downstream router, the router establishes a table,

e.g., a label information base (LIB). The following table illustrates an example LIB table for a

packet stream. The LIB table ties together the input port, the incoming MPLS label, the output

port and the outgoing port label.

Input Port	Incoming Port Label	Output Port	Outgoing Port Label
1	3	4	8

Fig. 6 illustrates a plurality of routers including a label-switched path and corresponding

label information base (LIB) tables for the label-switched path according to an embodiment of

the present invention. For example, the initial router R1 **42** may insert the MPLS label into the

first packet and forward the packet to R2 **44**. Each subsequent router examines the port label of

the received packet and replaces it with the outgoing label and forwards it to the next router. For

example, R3 **46** receives the packet from R2 **44**, examines the label of the received packet, e.g.,

9, replaces the label with the outgoing port label, e.g., 2, and sends the packet out port 8. When

the packet reaches the last router in the global network, the last router may remove the label

packet because it is exiting the MPLS domain and the label packet is no longer needed. The

subsequent packets sent by the VLAN of the first enterprise network follow the same MPLS LSP

in the global network as that of the first packet.

When the packets reach the last router of the global network, e.g., the egress router, the egress router identifies to which LAN switch the packet(s) are to be sent. The router determines which LAN switch is the destination of the packet by comparing the packet's IP destination address prefix to a routing table. The egress router then maps the IP address to a physical address. For example, a router may contain entries in a routing table similar to the following:

12.129.xx.xx = Direct Delivery => Means these addresses are connected to the network and the packets need to be delivered to a LAN switch to forward to these addresses.

23.32.xx.xx = Forward to Router 13 => Not directly on network.

27.52.xx.xx = Forward to Router 14 => Not directly on network.

If a packet arrives with an IP destination address of, for example, 12.129.2.3, then the egress router utilizes its routing table and determines if the address is somewhere on this physical network. If the router then finds the physical address through another lookup, or by using a protocol name address resolution protocol, the router sends it out over the physical enterprise LAN to the appropriate switch.

The last leg of the virtual circuit is completed by the establishment of a VLAN on the second or destination enterprise LAN. A network administrator, or software program, establishes the VLAN to include devices participating in the same application as the devices in the source enterprise LAN. The egress routing device on the global network is included in the destination enterprise LAN's VLAN to allow fast and secure travel through the destination enterprise network to the endsystems that are participating in the application.

As illustrated in Fig. 2(b), the second, or destination, enterprise LAN includes endsystems **54 58 60 62**, destination endsystem **56**, LAN switch S2 **50**, and LAN switch S3 **52**. Endsystems **54**, **56**, and **58** are connected to LAN switch S2 **50**. Endsystems **60** and **62** are

connected to LAN switch S3 **52**. In one embodiment of the invention, VLAN 25 includes router R4 **48**, endsystem **56**, endsystem **62**, LAN switch S2 **50** and LAN switch S3 **52**. In one embodiment of the invention, a network administrator constructs a VLAN-ID table in LAN switch S2 **50** for VLAN 25. Alternatively, a software program constructs a VLAN-ID table in LAN switch S2 **50** for VLAN 25. Note that since the enterprise networks are separate and distinct from each other, a new network administrator or software program is used to establish the VLAN.

When the LAN switch S2 **50** receives a packet from router R4 **48,** it retrieves from its VLAN endsystem table that VLAN-ID 25 is associated with router R4 **48**. LAN switch S2 **50** encapsulates the packet with a VLAN header indicating the packet is to be transmitted to members of VLAN 25. LAN switch S2 **50** also determines which ports are associated with VLAN 25 by accessing the VLAN port designation table. After determining which ports are associated with VLAN 25, S2 **50** transmits packets out of all the associated ports except for the port connected to R4 **48**. The transmission includes sending the packet(s) to LAN switch S3 **52** and endsystem **56**. Even though endsystem **62** is also on VLAN 25, it is not directly connected to LAN switch S2 **50** and is not entered into the S2's VLAN endsystem table.

When LAN switch S3 **52** receives the packet with the VLAN 25 header, LAN switch S3 **52** accesses its VLAN endsystem table to determine which endsystems are associated with VLAN-ID 25 and accesses the VLAN port designation table to determine with which ports the VLAN is associated. In one embodiment of the invention, LAN switch S3 **52** sends out the transmission on all of the ports associated with VLAN-ID 25 except for the incoming port. In one embodiment of the invention, LAN switch S3 **52** sends out the transmission to endsystem **62** since it is the only endsystem associated with VLAN-ID 25 connected to LAN switch S3 **52**.

12

Alternatively, LAN switch S3's **52** VLAN endsystem table may identify that all communications received from the specific port that is attached to LAN switch S2 are members of a separate VLAN, e.g., VLAN 35. In this example, LAN switch S3 **52** investigates its VLAN endsystem table to determine which endsystems are associated with VLAN 35 and checks its VLAN port designation table to determine which ports may receive the transmission. Therefore, if endsystem **56** is a member of VLAN 35, endsystem **56** receives the transmission.

In applications such as videoconferencing over the Internet and IP telephony, communication flows in both directions between parties. Therefore, an end-to-end virtual circuit needs to be established from the original destination enterprise LAN back to the original source enterprise LAN. The virtual circuit segments, e.g., the VLANs, in both the original destination and the original source enterprise LANs may be utilized in directing a communication from the new source (old destination) enterprise LAN over the global network to the new destination (old source) enterprise LAN. Alternatively, new VLANs may be established in the new source and new destination enterprise LANs to transmit the packets.

In one embodiment of the present invention, the communication may originate from endsystem **56**, which has now become the source endsystem for these communications. LAN switch S2 **50** receives the communication, understands the packet should be transmitted on VLAN-ID 25, and sends it out to all ports associated with VLAN-25. This VLAN-ID includes the port connected to R4 **48**. The same VLAN-ID may be utilized for both directions of the communication because the same application is directing the communication. Illustratively, the edge router on the global network, e.g., R4 **48**, receives the packet or packets and begins the process of establishing the virtual circuit through the global network back to a destination endsystem on the first enterprise LAN (the original source enterprise LAN.)

13

MPLS establishes only a one-way virtual circuit so a separate label-switched path (LSP) is established for communications flowing in the opposite direction. The edge router, e.g., R4 **48**, receives a packet from a LAN switch because the edge router is included in the VLAN-ID, e.g., VLAN 25. The VLAN-ID means all packets are treated in the same manner.

As discussed previously, router R4 **48** may determine the next hop in the network via a variety of methods. When the next hop is determined, the new ingress (old egress) router requests a label from the next router. This process continues until the path reaches the new egress router (old ingress router). The new egress router then passes a label to the router that requested the label from it. This process continues back to the new ingress router and forms the label-switched path (LSP). The LSP created for communication between the new ingress router and the new egress router does not have to utilize the same routers that the LSP between the old ingress router and the old egress router utilized. In other words, the routers utilized in the LSP for the traffic flowing from R4 **48** to R1 **42** do not have to be the same routers utilized in the LSP for the traffic flowing from R1 **42** to R4 **48**.

Fig. 4 illustrates a network of MPLS-enabled routers according to an embodiment of the present invention. In one embodiment of the invention, a LSP is created for packet traffic between R4 and R1. In one embodiment of the invention, the label switched path includes R4 **48**, R3 **46**, R2 **44** and R1 **42**. In another embodiment of the invention, the label switched path includes R4 **48**, R6 **66**, R5 **64**, and R1 **42**. In the embodiment where R4 **48** is the new ingress router and R1 **42** is the new egress router, R4 **48** places a label on the packet to instruct the router how to transmit the packet. R4 **48** accesses its LIB table to determine where the packet is to be transmitted and which port is to be utilized. R3 **46** examines the label from router R4 **48**, utilizes its LIB table to determine where the packet is to be sent, discards router R4's **48** label and inserts

its outgoing label on the packet. The process of investigating the incoming label and replacing

the outgoing label continues until the packet reaches the new egress router, e.g., R1 **42**.

The routing table in the new egress router R1 **42** then investigates the packet's destination

IP address to determine if the address is located on a network connected to the router, as

discussed previously. If the new address is located on the enterprise network connected to the

new egress router R1 **42**, the new egress router forwards the packet to the enterprise network. In

one embodiment of the invention, R1 **42** investigates the packet's destination IP address and

determines that the destination IP address is located on the enterprise LAN connected to R1 **42**

by LAN switch S1 **40** and transmits the packet to S1 **40**.

In one embodiment of the present invention, the LAN switch S1 40 receives the incoming

packet from router R1 **42** and identifies that the packet is associated with VLAN-ID 15 because

the packets were received on a port that is a member of VLAN-ID 15, e.g., port 4 in S1 **40**

connected to R1 **42**. S1 **40** investigates its VLAN endsystem table to establish that endsystem

34, endsystem **38** and router R1 **42** are members of VLAN 15. S1 **40** investigates its VLAN-

access port table to determine which ports should be utilized to transmit to the members of

VLAN-ID 15. After accessing the VLAN port designation table, S1 **40** transmits the packets to

both endsystem **34** and endsystem **38** on ports 1 and 3, respectively.

In an alternative embodiment of the invention, an enterprise LAN may include a plurality

of switches. The packets transmitted in the enterprise LANs may travel through all of the

switches contained in the intermediate enterprise LAN according to VLAN techniques discussed

previously. Alternatively, the packets may only travel through two or three of the LAN switches

included in the enterprise network. In addition, the plurality of switches may all utilize one

VLAN for the transmission of packets or the plurality of switches may utilize multiple VLANs for the transmission of packets.

Fig. 7 illustrates the transmission of a packet through an enterprise LAN including a plurality of switches by utilizing one VLAN and also by utilizing two VLANs according to an embodiment of the present invention. For example, VLAN 40 may be utilized throughout the plurality of switches with each switch having information regarding VLAN 40 in its VLAN endsystem table, and VLAN port designation table. Alternatively, endsystem 75 may transmit a packet as a member of VLAN 45 to LAN S10 76, which receives the information on port 4. LAN switch S10 76 may recognize that any packet received on port 4 is part of VLAN 50 and transmit the packet based on its VLAN table information for VLAN 50 to LAN switch S11 77, which receives the information on port 6. LAN switch S11 77 may recognize that any packet received on port 6 is part of VLAN 55 and transmit the packet based on its VLAN table information for VLAN 55 to LAN switch S12 78, which receives the information on port 8. LAN switch S12 78 may recognize that a packet received on port 8 involves VLAN 60 and may transmit the packet based on its VLAN table information for VLAN 60 to Router R1 79.

The present invention is not limited to an end-to-end virtual circuit including a source enterprise local area network (LAN), a plurality of routers, and a destination enterprise LAN. The secure virtual circuit may span multiple enterprise LANs connected together by routing segments. Fig. 8 illustrates a virtual circuit with multiple enterprise local area networks connected by multiple routing segments according to an embodiment of the present invention. The end-to-end virtual circuit (EEVC) spans enterprise LAN 1 80, routing segment 1 (RS1) 82, enterprise LAN 2 84, routing segment 2 (RS2) 86, enterprise LAN 3 88, routing segment 3 (RS3) 90, and enterprise LAN 4 92. VLANs are utilized in the first enterprise LAN 80, and the last

enterprise LAN **92,** to transmit packets as described previously. In each of the routing

segments, an MPLS label-switched path (LSP) is created to transmit the packets through the

routing segments, as discussed previously. Although the path the packets travel in the

intermediate enterprise LANs (ELAN 2 **84** and ELAN 3 **88**) is similar to the packet path in a

destination or source enterprise LAN, a description is helpful because the enterprise LANs are

now accepting packets of data and also transmitting packets of data.

A VLAN-ID is established to enable communications over an intermediate enterprise

LAN. In one embodiment of the invention, the VLAN includes the last router (egress router) on

the routing segment preceding the intermediate enterprise LAN, the switch on the intermediate

enterprise LAN, and the ingress router on the routing segment succeeding the intermediate

enterprise LAN. In one embodiment of the invention, an endsystem or a plurality of endsystems

may also be included in the VLAN with the preceding egress router, the LAN switch, and the

succeeding ingress router. For example, if users on endsystems that are connected to the LAN

switch on this intermediate LAN segment are participating in the application, (such as a

conference call), the users may receive the packets. The LAN switch on the intermediate

enterprise LAN receives the packet from the egress router of the preceding routing segment,

determines the router is part of a VLAN by utilizing its VLAN endsystem, and VLAN port

designation tables, and distributes the packet to members of the VLAN utilizing techniques

discussed previously. Because one of the members of the VLAN is the ingress router of the

succeeding routing segment, the packet/packets are transmitted to the ingress router.

Fig. 9 illustrates an intermediate enterprise local area network's (LAN's) transmission of

data packets from a preceding routing segment to a succeeding routing segment according to an

embodiment of the invention. Fig. 9 includes an egress router **94** of routing segment RS1 **82** (see

17

Fig. 8), a LAN switch S10 **96** located in enterprise LAN 2 **84**, and an ingress router **98** of routing

segment RS2 **86**. VLAN 25 includes egress router **94**, LAN switch S10 **96**, and ingress router **98**

as members of the VLAN. The data packet is transmitted from the egress router **94** to the LAN

switch S10 **96**. S10 **96** recognizes that router **94** is part of VLAN 25, determines what other

devices are associated with VLAN 25, determines what ports are associated with VLAN 25, and

transmits the data through these ports. In this embodiment of the present invention, the packet is

transmitted out of a switch port connected to ingress router **98** because it is a member of VLAN

25. After receiving the packet, the ingress router **98** starts the creating of the label-switched path

in routing segment 2 **86**.

The present invention involves an end-to-end virtual circuit that spans multiple

enterprise LANs and a global network. A transmission is established from a source endsystem to

a destination endsystem. The source endsystem is located on an enterprise local area network

(LAN). A VLAN-ID, that includes the ingress router of the global network, is established to

transport the packet from the source endsystem to the ingress router on the global network. The

global network includes MPLS-enabled routers. A label-switched path is established to transport

the packets from the ingress router to the egress router in the global network. A second VLAN-

ID, that includes the egress router of the global network, is established to transport the packet

from the egress router on the global network to the destination endsystem.

While the description above refers to particular embodiments of the present invention, it

will be understood that many modifications may be made without departing from the spirit

thereof. The accompanying claims are intended to cover such modifications as would fall within

the true scope and spirit of the present invention. The presently disclosed embodiments are

therefore to be considered in all respects as illustrative and not restrictive, the scope of the

18

invention being indicated by the appended claims, rather than the foregoing description, and all

changes that come within the meaning and range of equivalency of the claims are intended to be

embraced therein.